

2-CHANNEL

Constant Current LED Driver

**Model Number
AC-DI8C350UVH**

Input Voltage: 120-277V


Input Frequency: 50/60Hz

Side Mount/Leads

ELECTRICAL SPECIFICATIONS:


Output Power Max.	Input Power	Input Current	Min PF (full load)	Max THD (full load)	Output Voltage	Output Current	T case Max	Minimum Starting Temp	Efficiency Up To
36W	42W	0.34A @ 120V 0.17@ 277V	>0.92	<25%	31-51V	350mA±5%	90° C	-40° C	80.1%

WIRING:



Lead Lengths	
White	5.9"
Black	5.9"
Red	5.9"
Blue	5.9"
Brown	5.9"
Yellow	5.9"

PHYSICAL:



Dimensions	
Length	6.77"
Width	2.4"
Height	1.22"
Mounting Length	6.22"
Weight	0.84 lbs.
Case Qty.	40 pcs.

SAFETY:

- UL and cUL Recognized
- Class 2
- UL Outdoor Type I
- Class A sound rating
- Overload Protection
- Open/Short Circuit Protection
- LED driver has a life expectancy of 50,000 hours at Tcase of ≤75°C
- LED driver has a life expectancy of 100,000 hours at Tcase of ≤65°C
- Warranty: 5 yrs based on max case temp of <75°C; 3 yrs based on max case temp of 90°C*
- Input/Output Isolation
- FCC Title 47 CFR Part 15
- Surge Protection (3 Kv)

INSTALLATION:

- LED drivers shall be installed inside electrical enclosures
- 18 AWG 600V/105C tinned strand copper lead-wires are required for installation
- Max Remote installation distance is 18 ft
- LED driver cases should be grounded



*AC Electronics/AC LED Power Designs warrants to the purchaser that each LED Driver will be free from defects in material or workmanship for a period of 5 years when operated at max case temp of up to <75°C; 3 years from date of manufacture when operated at a max case temp of up to 90°C when properly installed and under normal conditions of use. See aceleds.com for complete warranty policy.



3401 Avenue D, Arlington, TX 76011 • 800-375-6355 • www.aceleds.com

Data is based upon tests performed by AC Electronics in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.

