"Match-Book Sized"
LED Driver Family

The Smallest Possible Factors™

LISTED
E332747

TRIAC/Phase Cut Dimming Leading Edge Dimming Driver

Constant Current LED Driver

Model Number AC25CT700KT2Q

Input Voltage: 120 VAC (±10%)
Input Frequency: 60 Hz
Dimming: Leading Edge TRIAC
Surge Protection: 2 Kv
Side Mount/Leads
Multi-Switching Current

PHYSICAL DIMENSIONS:

Length: 2.88"
Width: 1.43"
Height: 1.07"
Mounting: 2.68"
Weight: 0.15 lbs.

ACTUAL SIZE

ELECTRICAL SPECIFICATIONS:

Output Power Max	Input Power	Input Current	Min. PF (full load)	Max. THD (full load)	Output Voltage	Output Current	T case Max.	Min. Starting Temps.	IP Rating	Dimming Protocol	Dimming Range	Efficiency Up To
25 W	28.6 W	0.27 A @ 120 V	>0.9	<20	22-36 V	700 mA ±5%	75° C	0° C	20	Phase Cut	≤5 to 100% Dim-to-Off	83%
18 W	20.5 W	0.17 A @ 120 V	>0.9	<20	22-36 V	500 mA ±5%	75° C	0° C	20	Phase Cut	≤5 to 100% Dim-to-Off	83%
12.6 W	14.7 W	0.12 A @ 120 V	>0.9	<20	22-36 V	350 mA ±5%	75° C	0° C	20	Phase Cut	≤5 to 100% Dim-to-Off	83%

WIRING:

Leading Edge



LEAD LENGTH:

Black	6"	Blue	6"
White	6"	Red	6"

APPROVED DIMMERS:

**Dimmer Compatibility Chart on page 2

To order or consult with one of our engineers, contact us at:
800-375-6355 / aceleds.com

ACE LEDS

©2023 27Mar2023

SAFETY & PERFORMANCE:

- Class P Listed
- Class A sound rating
- No PCBs
- Open/Short Circuit Protection
- LED driver has a life expectancy of 50,000 hours at Tcase of ≤75°C
- Warranty: 5 yrs based on max case temp of 75°C*
- Input/Output Isolation
- Surge Protection (2 KV)
- Title 24 Compatible (Depending on LED)
- FCC part 15 Class B (Without Dimmer)
- Class 2

INSTALLATION:

- LED drivers shall be installed inside electrical enclosures
- Max Remote installation distance is 33 ft
- 22 AWG 600V/105C tinned stranded copper lead-wires are required to use in installation

*ACE LEDS/AC LED Power Designs warrants to the purchaser that each LED Driver will be free from defects in material or workmanship for a period of 5 years from date of manufacture when operated at max case temp of up to ≤75°C when properly installed and under normal conditions of use. See aceleds.com for complete warranty policy.

LEADING EDGE DIMMER COMPATIBILITY

Manufacturer	Model	Dimming Type
Leviton	6674	LEADING
Leviton	6684	LEADING
Leviton	RPI06	LEADING
Leviton	IPI06	LEADING
Lutron	NTLV-600	LEADING
Lutron	DV-103P	LEADING
Lutron	Skylark S-600P	LEADING
Lutron	DVCL-153P	LEADING

****Dimming Rate variable depending on Dimmer and LED Light source**

3401 Avenue D, Arlington, TX 76011
800-375-6355 • aceleds.com

c UL us LISTED E332747

Data is based upon tests performed by ACE LEDS in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.
All specifications are nominal unless otherwise noted.

RoHS COMPLIANT LEAD-FREE

ACE LEDS

©2023 27Mar2023

PERFORMANCE METRICS: AC25CT700KT2Q



Efficiency Vs. Output Power



Power Factor Vs. Output Power



THD Vs Output Power

3401 Avenue D, Arlington, TX 76011
800-375-6355 • aceleds.com

Data is based upon tests performed by ACE LEDS in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.
All specifications are nominal unless otherwise noted.

c UL us LISTED E332747

RoHS COMPLIANT LEAD-FREE

ACE LEDS

©2023 27Mar2023